

**LED PARKING GARAGE LIGHT
62-WATT LED
(E.PG2L SERIES)**

Applications: For use in parking garage structures

Typical Mounting Height: 8 to 15 feet **Typical Spacing:** 3 to 4 times the mounting height



11-3/8" H x 13" W x 13" D
Weight: 12 lbs.

Catalog #	Description	Input Voltage	Initial Delivered Lumens	CCT	CRI	50K Hours Projected Lumen Maintenance Factor at 25°C ¹	Comparable To
E.PG2L06CS	62W LED, Cool White	120V-277V	5600	5000K	74	96%	175W MH

¹Calculated L₇₀ based on 6,048 hours of LM-80 testing: >36,000 hours

Features

Performance

- Estimated 100,000 hours of maintenance-free operation to L₇₀ at 25°C (77°F)
- Minimum starting temperature: -40°C (-40°F)
- 5-year limited warranty

Construction & Materials

- Aluminum housing
- Silver polyester powder coat
- Polycarbonate lens
- Mounts flush to standard J-box, surface mount conduit or 1/2" conduit entry on top for pendant mounting using NPT threaded pipe
- Cree® LEDs inside

Electrical

- Non-dimmable
- Universal voltage (120V through 277V)
- Amperage Draw: 0.53A at 120V
0.31A at 208V
0.28A at 240V
0.25A at 277V
- > 0.9 power factor
- < 20% total harmonic distortion

Regulatory

- ETL Listed for wet locations



INTEGRATED LIGHTING SOLUTIONS

© 2015 Cree, Inc. and/or one of its subsidiaries. All rights reserved. For informational purposes only. Content is subject to change. Cree® is a registered trademark, and the Cree logo is a trademark of Cree, Inc. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.