


# RECESSED LED CANOPY LIGHT - WIDE DISTRIBUTION 42-WATT LED (E.RC2L04CW)

**Applications:** Security, pathway and perimeter lighting. Also recommended for walkways and exterior canopies.


**Typical Mounting Height:** 8 to 15 feet    **Typical Spacing:** 1 to 2 times the mounting height



2-2/3"H x 16"W x 16"D    Weight 6.2 lbs.  
(Recessed housing is an 8" square)



LED PATTERN



DISTRIBUTION PATTERN  
Bird's Eye View, Ceiling Mounted

Catalog #	Description	Input Voltage	Delivered Lumens	CCT	CRI	Lifetime (L <sub>70</sub> at 25° C)
<b>E.RC2L04CW</b>	42W LED Cool white	120V-277V	4100 Lumens	5000K	75	50,000 Hours

## Features

- 0-10V Dimmer
- 50,000 hours of maintenance-free operation to L<sub>70</sub> at 25° C
- 75 CRI
- Rugged and durable aluminum housing
- Non-IC rated
- White polyester powder-coat finish
- Minimum starting temperature: -22° F
- UV-stabilized acrylic lens with molded precision optics
- Two 1/2" conduit entries on top for through wiring
- Hanging cable supports fixture while wiring connections are made
- Secures to mounting surface with four screws (provided by others)
- RoHS compliant
- Universal voltage (120V through 277V)
- ETL Listed for wet locations
- Cree® LEDs inside
- Five-year limited warranty. Certain exclusions apply.  
For details, visit [www.cree.com/lighting/ILS](http://www.cree.com/lighting/ILS)



This fixture is listed on the DesignLights Consortium® Qualified Products List.

## Accessories

None Available



INTEGRATED LIGHTING SOLUTIONS

© 2014 Cree, Inc. All Rights Reserved. The information in this document is subject to change without notice. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.