

# LED CANOPY LIGHT - WIDE DISTRIBUTION 36-WATT LED (E.CC5L SERIES)

**Applications:** Security, entryway and perimeter lighting. Also recommended for parking garages, shopping area walkways, and exterior canopies

**Typical Mounting Height:** 8 to 15 feet    **Typical Spacing:** 1 to 2 times the mounting height



3-15/16"H x 9-7/8"W x 9-7/8"D    Weight 5 lbs.

Catalog #	Description	Input Voltage	Delivered Lumens	CCT	CRI	50K Hours Projected Lumen Maintenance Factor at 25°C
<b>E.CC5L03CW</b> (white) <b>E.CC5L03CZ</b> (dark bronze)	36W LED Cool white	120V-277V	3618 Lumens	5000K	≥70	79%
<b>E.CC5L03NW</b> (white) <b>E.CC5L03NZ</b> (dark bronze)	36W LED Neutral white	120V-277V	3662 Lumens	4000K	≥70	79%

## Features

- 76,000 hours of maintenance-free operation to L<sub>70</sub> at 25°C
- Minimum starting temperature: -40° F
- Non-dimmable
- Universal voltage (120V through 277V)
- 75°C minimum supply wire required
- Low copper, die-cast aluminum housing
- White or dark bronze polyester powder-coat finish
- UV-stabilized acrylic prismatic refractor with self retaining screws
- 3/4" conduit entry on top for pendant mounting
- 1/2" conduit entries on two sides
- UL Listed for wet locations
- Cree® LEDs inside
- Five-year limited warranty. Certain exclusions apply.  
For details, visit [www.cree.com/lighting/ILS](http://www.cree.com/lighting/ILS)

## Accessories

None Available



INTEGRATED LIGHTING SOLUTIONS

© 2014 Cree, Inc. All Rights Reserved. The information in this document is subject to change without notice. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.