

LED CANOPY LIGHT - WIDE DISTRIBUTION 38-WATT LED (E.CC3L SERIES)

Applications: Security, entryway and perimeter lighting. Also recommended for parking garages, shopping area walkways, and exterior canopies

Typical Mounting Height: 8 to 15 feet **Typical Spacing:** 1 to 2 times the mounting height



(White)

3-15/16"H x 9-7/8"W x 9-7/8"D Weight 5 lbs.

Catalog #	Description	Input Voltage	Delivered Lumens	CCT	CRI	Lifetime (L ₇₀ at 15°C)
E.CC3L03NW (white)	38W LED Neutral white	120V-277V	2000 Lumens	4100K	77	50,000 Hours

Features

- 50,000 hours of maintenance-free operation to L₇₀ at 15°C
- Non-dimmable
- Low copper, die-cast aluminum housing
- White polyester powder-coat finish
- UV-stabilized acrylic prismatic refractor with self retaining screws
- 75°C minimum supply wire required
- 3/4" conduit entry on top for pendant mounting
- 1/2" conduit entries on two sides
- Universal voltage (120V through 277V)
- Minimum starting temperature: -40°F
- Heat dissipating fins
- RoHS compliant
- UL Listed for wet locations
- Cree® LEDs inside
- Three-year limited warranty. Certain exclusions apply. For details, visit www.cree.com/lighting/ILS

Accessories

None Available



INTEGRATED LIGHTING SOLUTIONS

© 2014 Cree, Inc. All Rights Reserved. The information in this document is subject to change without notice. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.