

## PREMIUM LED FLOODLIGHT – SMALL 72-WATT LED (E.HL5 SERIES)

**Applications:** Building facades, displays, uplighting and signs. Also effective as security lighting, for storage areas and commercial sites.

**Typical Mounting Height:** 8 to 20 feet



12-1/4"H x 10-3/4"W x 6"D Weight 8.4 lbs. (Height dimension includes fitter)

Catalog #	Description	Input Voltage	Delivered Lumens	Beam Angle/ Photometric Distribution	CCT	CRI	Lifetime (L <sub>70</sub> at 15°C)
<b>E.HL5F06C2Z</b>	72W LED Cool white	120V-277V	6150 Lumens	40° Flood	5000K	70	50,000 Hours
<b>E.HL5F06N2Z</b>	72W LED Neutral white	120V-277V	6150 Lumens	40° Flood	4000K	70	50,000 Hours
<b>E.HL5S06C2Z</b>	72W LED Cool white	120V-277V	6150 Lumens	20° Spot	5000K	70	50,000 Hours
<b>E.HL5S06N2Z</b>	72W LED Neutral white	120V-277V	6150 Lumens	20° Spot	4000K	70	50,000 Hours

### Features

- 50,000 hours of maintenance-free operation to L<sub>70</sub> at 15°C
- Non-dimmable
- Die-cast aluminum housing and lens frame
- Dark bronze polyester powder-coat finish
- Tempered glass lens, thermal shock and impact resistant
- Minimum starting temperature: -40°F
- 1/2" NPS adjustable fitter included
- Universal voltage (120V through 277V)
- Precise optical reflector
- Heat dissipating fins
- Suitable for ground mounting, uplighting & downlighting
- RoHS compliant
- UL Listed for wet locations
- Cree® LEDs inside
- Five-year limited warranty. Certain exclusions apply.  
For details, visit [www.cree.com/lighting/ILS](http://www.cree.com/lighting/ILS)

### Accessories

None Available



INTEGRATED LIGHTING SOLUTIONS

© 2014 Cree, Inc. All Rights Reserved. The information in this document is subject to change without notice. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.