

TRADITIONAL STYLE LED WALL PACK 96-WATT LED (LARGE) (E.WP9L SERIES)

Applications: Security, pathway and perimeter lighting; ideal for entryways and walkways.
Typical Mounting Height: 12 to 20 feet **Typical Spacing:** 2 to 3 times the mounting height



9-3/4"H x 18"W x 9-3/8"D Weight 15.8 lbs.

| Catalog # | Description | Input Voltage | Delivered Lumens | CCT | CRI | Lifetime (L ₇₀ at 25° C) |
|-------------------|--------------------------|---------------|------------------|-------|-----|-------------------------------------|
| E.WP9L09CZ | 96W LED Cool white | 120V-277V | 6300 Lumens | 5000K | 70+ | 76,000 Hours |
| E.WP9L09NZ | 96W LED Neutral white | 120V-277V | 5600 Lumens | 4000K | 70+ | 76,000 Hours |

Features

- Non-dimmable
- Estimated 76,000 hours of maintenance-free operation to L₇₀ at 25° C
- Universal voltage (120V through 277V)
- Heavy duty, die-cast aluminum housing with hinged door frame
- Dark-bronze polyester powder-coat finish
- Heat- and shock-resistant borosilicate glass prismatic lens
- Ambient operating temperature: -22°F to 104°F
- 1/2" NPT tapped knockouts for conduit entrances (one on top, one on each side, one on back)
- Optional photocell available
- RoHS compliant
- UL Listed for wet locations
- Cree® LEDs inside
- Five-year limited warranty. Certain exclusions apply. For details, visit www.cree.com/lighting/ILS

Accessories

None Available