

SMALL LED FLOODLIGHT 9-WATT LED (E.GL3L SERIES)

Applications: Security, building facades, displays, signs, and other residential uses.
Typical Mounting Height: 8 to 15 feet



4"H x 4"W x 4-5/8"D Weight 0.8 lbs.

Catalog #	Description	Input Voltage	Delivered Lumens	CCT	CRI	Lifetime
E.GL3L09N2K (Black)	9W LED Neutral white	120V-277V	700 Lumens	4000K	80	50,000 Hours
E.GL3L09N2W (White)						

Features

- 50,000 hours of maintenance-free operation
- Non-dimmable
- 9W LED
- 700 lumens, comparable to 50W halogen
- Neutral white (4000K) color temperature at 80 CRI
- Low-copper, die-cast aluminum housing and lens frame
- Textured black or smooth white polyester powder-coat finish
- 1/2-inch NPS aluminum die-cast swivel fitter attaches to standard J-box
- Tempered glass lens, thermal shock and impact resistant
- Universal voltage (120V through 277V)
- Minimum starting temperature: -22°F
- UL Listed for wet locations
- Cree® LEDs inside
- Five-year limited warranty. Certain exclusions apply. For details, visit www.cree.com/lighting/ILS

Accessories

None Available



INTEGRATED LIGHTING SOLUTIONS

© 2014 Cree, Inc. All Rights Reserved. The information in this document is subject to change without notice. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.