

LED COMPACT FLOODLIGHT 30-WATT LED (E.CF3L SERIES)

Applications: General purpose floodlight that's perfect for building facades, display, uplighting, and signs. Also effective as security lighting for storage areas and commercial sites.

Typical Mounting Height: 8 to 15 feet



6"H x 7-3/4"W x 4-3/4"D Weight 3 lbs.

Catalog #	Description	Input Voltage	Delivered Lumens	CCT	CRI	Lifetime (L ₇₀ at 25°C)
E.CF3L03C2Z (dark bronze) E.CF3L03C2W (white)	30W LED, Cool White	120V-277V	3000 Lumens	5000K	70	76,000 Hours
E.CF3L03N2Z (dark bronze) E.CF3L03N2W (white)	30W LED, Neutral White	120V-277V	3000 Lumens	4000K	70	76,000 Hours

Features

- Estimated 76,000+ hours of maintenance-free operation to L70 at 25°C
- Non-dimmable
- Durable die-cast aluminum housing
- Polyester powder coat white or dark-bronze finish for extra corrosion protection
- Tempered glass lens, thermal shock and impact resistant
- Minimum starting temperature: -40°F
- Universal voltage (120V-277V)
- 1/2-inch NPS die-cast swivel fitter included
- UL Listed for wet locations
- Cree® LEDs inside
- Five-year limited warranty. Certain exclusions apply. For details, visit www.cree.com/lighting/ILS

Accessories

None Available



INTEGRATED LIGHTING SOLUTIONS

© 2015 Cree, Inc. All Rights Reserved. The information in this document is subject to change without notice. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.