

SMALL LED FLOODLIGHT 21-WATT LED (E.CF2L SERIES)

Applications: Security, building facades, displays, signs, and other residential uses.
Typical Mounting Height: 8 to 15 feet



4-3/4"H x 6-1/8"W x 4-3/4"D Weight 2 lbs.

Catalog #	Description	Input Voltage	Delivered Lumens	CCT	CRI	Lifetime (L ₇₀ at 25° C)
E.CF2L21N2Z (dark bronze) E.CF2L21N2W (white)	21W LED Neutral white	120V-277V	1600 Lumens	4000K	80	50,000 Hours

Features

- 50,000 hours of maintenance-free operation
- Non-dimmable
- 21W LED
- 1600 lumens, comparable to 50W PSMH
- Neutral white (4000K) color temperature at 80 CRI
- Low-copper, die-cast aluminum housing and lens frame
- Dark bronze or white polyester powder-coat finish
- 1/2-inch NPS aluminum die-cast swivel fitter attaches to standard J-box
- Tempered glass lens, thermal shock and impact resistant
- Universal voltage (120V through 277V)
- Minimum starting temperature: -22° F
- UL Listed for wet locations
- Cree® LEDs inside
- Five-year limited warranty. Certain exclusions apply. For details, visit www.cree.com/lighting/ILS

Accessories

None Available



INTEGRATED LIGHTING SOLUTIONS

© 2014 Cree, Inc. All Rights Reserved. The information in this document is subject to change without notice. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.