

## LED GOOSENECK 15-WATT LED (E.DG1L SERIES)

**Applications:** Business storefronts, restaurants, and building perimeters that need an architectural touch of style

**Typical Mounting Height:** 8 to 15 feet



**Straight Shroud**  
31.5"L x 15.3"W x 18.8"H  
Weight: 5.0 lbs.



**Angled Shroud**  
35"L x 15.3"W x 25.8"H  
Weight: 5.0 lbs.

Catalog #	Description	Input Voltage	Delivered Lumens	CCT	CRI	50K Hours Projected Lumen Maintenance Factor at 25°C <sup>1</sup>
<b>E.DG1L13UAK</b>	15W LED, Warm White, Angled Shroud	120V-277V	1100	3000K	≥70	88%
<b>E.DG1L13USK</b>	15W LED, Warm White, Straight Shroud	120V-277V	1260	3000K	≥70	88%

<sup>1</sup> Calculated L<sub>70</sub> based on 6,048 hours of LM-80 testing: >36,000 hours

### Features

- Non-dimmable
- Estimated 150,000+ hours of maintenance-free operation to L<sub>70</sub>
- Universal voltage (120V through 277V)
- Die-cast aluminum mounting box and housing
- Supplied with back mounting plate to mount over a 4" square or octagonal j-box
- Black polyester powder-coat finish for extra corrosion protection and long-lasting color
- -30°C (-22°F) Minimum starting temp
- Tempered glass lens, thermal, shock and impact resistant
- ETL Listed for wet locations
- Cree® LEDs inside
- Five-year limited warranty. Certain exclusions apply. For details, visit [www.cree.com/lighting/ILS](http://www.cree.com/lighting/ILS)



INTEGRATED LIGHTING SOLUTIONS

© 2014 Cree, Inc. and/or one of its subsidiaries. All rights reserved. For informational purposes only. Content is subject to change. Cree® and the Cree logo are registered trademarks of Cree, Inc. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.