

**LED GOOSENECK
15-WATT LED
(E.DG1L SERIES)**

Applications: Business storefronts, restaurants, and building perimeters that need an architectural touch of style

Typical Mounting Height: 8 to 15 feet



Straight Shroud
31.5"L x 15.3"W x 18.8"H
Weight: 5.0 lbs.



Angled Shroud
35"L x 15.3"W x 25.8"H
Weight: 5.0 lbs.

Catalog #	Description	Input Voltage	Delivered Lumens	CCT	CRI	50K Hours Projected Lumen Maintenance Factor at 25°C ¹
E.DG1L13UAK	15W LED, Warm White, Angled Shroud	120V-277V	1100	3000K	≥70	88%
E.DG1L13USK	15W LED, Warm White, Straight Shroud	120V-277V	1260	3000K	≥70	88%

¹ Calculated L₇₀ based on 6,048 hours of LM-80 testing: >36,000 hours

Features

- Non-dimmable
- Estimated 150,000+ hours of maintenance-free operation to L₇₀
- Universal voltage (120V through 277V)
- Die-cast aluminum mounting box and housing
- Supplied with back mounting plate to mount over a 4" square or octagonal j-box
- Black polyester powder-coat finish for extra corrosion protection and long-lasting color
- -30°C (-22°F) Minimum starting temp
- Tempered glass lens, thermal, shock and impact resistant
- ETL Listed for wet locations
- Cree® LEDs inside
- Five-year limited warranty. Certain exclusions apply. For details, visit www.cree.com/lighting/ILS



INTEGRATED LIGHTING SOLUTIONS

© 2014 Cree, Inc. and/or one of its subsidiaries. All rights reserved. For informational purposes only. Content is subject to change. Cree® and the Cree logo are registered trademarks of Cree, Inc. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.