

LED HIGH BAY ALUMINUM REFLECTOR 113- OR 225-WATT LED (E.AB1L SERIES)

Applications: Warehouses, industrial and retail sites
Typical Mounting Height: 15 to 30 feet



113W
16"L x 16"W x 12.9"H
Weight: 13.0 lbs.

225W
16"L x 16"W x 15.5"H
Weight: 17.0 lbs.

Catalog #	Description	Input Voltage	Delivered Lumens	CCT	CRI	50K Hours Projected Lumen Maintenance Factor at 25°C ¹
E.AB1L11NU	110W LED, Neutral White	120V-277V	11,263	4000K	≥70	79%
E.AB1L22NU	220W LED, Neutral White	120V-277V	20,736	4000K	≥70	79%

¹ Calculated L₇₀ based on 6,048 hours of LM-80 testing: >36,000 hours

Features

- Estimated 76,000 hours of maintenance-free operation to L70
- Non-dimmable
- Durable die-cast aluminum heat sink and housing
- White polyester powder-coat finish
- Tempered glass lens protects LEDs against dust and dirt
- 16" spun aluminum reflector
- -30°C (-22°F) Minimum starting temperature
- Suitable for ambient temperatures up to 40°C (104°F)
- 75°C Minimum supply wire required
- Universal voltage (120V through 277V)
- UL listed for damp locations
- Included slide splice box mounts directly over junction box or with 3/4" pendant (provided by others). Splice box has six 1/2" and two 3/4" knockouts on the sides.
- Cree® LEDs inside
- Five-year limited warranty. Certain exclusions apply. For details, visit www.cree.com/lighting/ILS



INTEGRATED LIGHTING SOLUTIONS

© 2014 Cree, Inc. and/or one of its subsidiaries. All rights reserved. For informational purposes only. Content is subject to change. Cree® and the Cree logo are registered trademarks of Cree, Inc. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.