

2'X2' LED TROFFER 38-WATT LED (E.TR22L2 SERIES)

Applications: For use in office, educational, retail, commercial and institutional applications



3-3/4" **H** x 23-5/8" **W** x 23-5/8" **L**
Weight: 13.2 lbs.

Catalog #	Description	Input Voltage	Delivered Lumens	CCT	CRI	50K Hours Projected Lumen Maintenance Factor at 25°C ¹	Comparable To
E.TR22L2383U	38W LED, Warm White	120V-277V	3700	3500K	82	75%	2 x F32T8/U6
E.TR22L2384U	38W LED, Neutral White	120V-277V	3800	4000K	82	75%	2 x F32T8/U6

¹ Calculated L₇₀ based on 6,000 hours of LM-80 testing: >36,000 hours

Features

Performance

- Estimated 60,000 hours of maintenance-free operation to L₇₀ at 25°C (77°F)
- Minimum starting temperature: -18°C (0°F)
- 5-year limited warranty

Construction & Materials

- Durable steel construction
- IC-rated for direct contact with insulation
- White polyester powder-coat finish
- Precision engineered polystyrene diffuser prevents hot spots shadows and glare while providing uniform illumination
- Installs into conventional grid ceiling
- Sealed, maintenance-free fixture design

Electrical

- 0-10V Dimming (see below for recommended dimmers)
- 120V through 277V Operation
- > 0.9 power factor
- < 20% total harmonic distortion
- Amperage Draw: 0.32A at 120V
0.18A at 208V
0.16A at 240V
0.14A at 277V

Regulatory

- UL Listed for damp locations

Recommended Dimmers

- Lutron NTSTV-DV

NOTE: The presence of a dimmer on this chart is not a guarantee or warranty of the compatibility of the fixture in any particular installation. The absence of a dimmer from this chart does not necessarily imply incompatibility.



INTEGRATED LIGHTING SOLUTIONS

© 2015 Cree, Inc. and/or one of its subsidiaries. All rights reserved. For informational purposes only. Content is subject to change. Cree® is a registered trademark, and the Cree logo is a trademark of Cree, Inc. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.