

# PREMIUM LED WALL PACK – SMALL 72-WATT LED (E.WP7L SERIES)

**Applications:** Security, pathway and perimeter lighting; ideal for entryways and other applications where control of spill light is important.

**Typical Mounting Height:** 8 to 20 feet **Typical Spacing:** 1 to 2 times the mounting height



5-3/4"H x 13"W x 11-3/4"D Weight 13.6 lbs.

Catalog #	Description	Input Voltage	Delivered Lumens	CCT	CRI	Lifetime (L <sub>70</sub> at 25°C)
<b>E.WP7L06CZ</b>	72W LED Cool White	120V-277V	6000 Lumens	5000K	70	50,000 Hours
<b>E.WP7L06NZ</b>	72W LED Neutral White	120V-277V	6000 Lumens	4000K	70	50,000 Hours

## Features

- 50,000 hours of maintenance-free operation to L<sub>70</sub> at 25°C
- Non-dimmable
- Low copper, die-cast aluminum housing and lens frame
- Dark bronze polyester powder-coat finish
- Fixed cutoff glare shield to reduce light pollution
- Tempered glass lens, thermal shock and impact resistant
- Patented lens design delivers true IES Type III distribution
- Mounts over recessed junction box or with conduit
- Die-cast detachable back box for easy mounting
- 75°C minimum supply wire required
- Universal voltage (120V through 277V)
- Minimum starting temperature: -40°F
- Heat dissipating fins
- Conduit entries on all sides of the fixture
- Two knockouts provided on back for conduit or J-box mounting
- RoHS compliant
- UL Listed for wet locations
- Cree® LEDs inside
- Five-year limited warranty. Certain exclusions apply. For details, visit [www.cree.com/lighting/ILS](http://www.cree.com/lighting/ILS)

## Accessories



Photocell is field installed. Drilling of the back box in the field is required.

**CAT.#: E.ACP1** (120 volts)

**CAT.#: E.ACP2** (208/240/277 volts)



INTEGRATED LIGHTING SOLUTIONS

© 2014 Cree, Inc. All Rights Reserved. The information in this document is subject to change without notice. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.