

TRADITIONAL STYLE LED WALL PACK 47-WATT LED (SMALL) (E.WP8L SERIES)

Applications: Security, pathway and perimeter lighting; ideal for entryways and walkways.
Typical Mounting Height: 8 to 15 feet **Typical Spacing:** 2 to 3 times the mounting height



9-1/4"H x 14-1/8"W x 7-1/2"D Weight 8.6 lbs.

Catalog #	Description	Input Voltage	Delivered Lumens	CCT	CRI	Lifetime (L ₇₀ at 25° C)
E.WP8L05CZ	47W LED Cool white	120V-277V	3200 Lumens	5000K	70+	76,000 Hours
E.WP8L05NZ	47W LED Neutral white	120V-277V	2900 Lumens	4000K	70+	76,000 Hours

Features

- Non-dimmable
- Estimated 76,000 hours of maintenance-free operation to L₇₀ at 25° C
- Universal voltage (120V through 277V)
- Heavy duty, die-cast aluminum housing with hinged door frame
- Dark-bronze polyester powder-coat finish
- Heat- and shock-resistant borosilicate glass prismatic lens
- Ambient operating temperature: -22°F to 104°F
- 1/2" NPT tapped knockouts for conduit entrances (one on top, one on each side, one on back)
- Optional photocell available
- RoHS compliant
- UL Listed for wet locations
- Cree® LEDs inside
- Five-year limited warranty. Certain exclusions apply. For details, visit www.cree.com/lighting/ILS

Accessories



Photocell is field installed. Drilling of the back box in the field is required.

CAT.#: E.ACP1 (120 volts)

CAT.#: E.ACP2 (208/240/277 volts)



INTEGRATED LIGHTING SOLUTIONS

© 2015 Cree, Inc. All Rights Reserved. The information in this document is subject to change without notice. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.